WAAS CH 70624 W26A	APP CRS 259°	Rwy Idg 4151 TDZE 1005 Apt Elev 1014

RNAV (GPS) RWY 26L
BRACKETT FIELD (POC)

RNP APCH.

Baro-VNAV and VDP NA when using Ontario altimeter setting. Rwy 26L helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Ontario Intl altimeter setting and increase all DA 32 feet and all MDA 40 feet, increase LPV and LNAV/VNAV all Cats visibility ⅛ SM. Circling NA for Cat C north of Rwy 8L-26R. Circling to Rwy 8L NA at night. When Circling to Rwy 8R at night, operational VGSI required, remain on or above VGSI glidepath until threshold.

MISSED APPROACH: Climb to 2100 then climbing left turn to 4000 direct PRADO and hold.

ATIS	SOCAL APP CON	BRACKETT TOWER★ RWY 8R/26L	BRACKETT TOWER★ RWY 8L/26R	GND CON	CLNC DEL	UNICOM
124.4	125.5 318.2	118.2 (CTAF)	133.3	125.0	121.875	122.95



Procedure NA for arrivals on PDZ VORTAC airway radials 278 CW 078.

ELEV 1014 TDZE 1005



REIL Rwys 8R and 26L
MIRL Rwy 8R-26L



CATEGORY	A	B	C	D
LPV DA	1305-⅞ 300 (300-⅞)			NA
LNAV/VNAV DA	1444-1¼ 439 (500-1¼)			NA
LNAV MDA	1500-1 495 (500-1)		1500-1⅜ 495 (500-1⅜)	NA
C CIRCLING	1680-1 666 (700-1)		1760-2¼ 746 (800-2¼)	NA

SW-3, 23 MAY 2019 to 20 JUN 2019
SW-3, 23 MAY 2019 to 20 JUN 2019